

## Military Electrical Grade Switchboard Matting

Type I, Type II, and Type III



Berry  
Amendment  
Compliant

### Switchboard Matting Engineered for all Divisions within the Department of Defense

**RM Biltrite™ Tuff Trac® Military Electrical Grade (MEG) Switchboard Matting** is manufactured with a combination of flame retardants and smoke suppressants to meet stringent flame and smoke density standards required for MIL-DTL-15562G specifications. All military grade rolls are marked on the backside with the specification, month, and year of manufacture to guarantee compliance with MIL-DTL-15562G requirements.

**Type I:** Smooth sheet; comes in a marbled beige, black\*, blue, green, grey, and terra cotta color. Typically used as floor covering for glue down installations in high voltage areas. Can be installed with heat or chemically sealed seams to create a watertight protective surface.

**Type II:** Smooth runner; comes in beige, black\*, blue, green, grey, and terra cotta color. Designed for single strip use as portable floor mats around electrical devices or electrical areas. Provides the same insulation and fire/smoke resistance as Type I.

**Type III:** Mat/runner with raised diamond plate finish; comes in beige, black\*, blue, green, grey, and terra cotta color. Designed to be used as a removable runner around electrical equipment or areas where electrical hazards may exist. Provides extra slip protection and the same insulation and fire/smoke resistance as Type I.

**\*Note:** Black is not authorized for use aboard submarines.


Type I  
Marbled

Type II  
Smooth

Type III  
Diamond

MEG SWITCHBOARD SPECIFICATIONS	TYPE I	TYPE II	TYPE III
Thickness:	1/8" (3.2 mm)	1/8" (3.2 mm)	3/16" (4.8 mm)
Durometer:	95 ± 5	75 (min)	65 (min)
Tensile Strength (initial):	800 psi (5.5 MPa)	800 psi (5.5 MPa)	800 psi (5.5 MPa)
Ultimate Elongation (min):	75%	100%	100%
Permanent Set (max):	25%	25%	25%
Dielectric Test Voltage:	30,000 VAC	30,000 VAC	30,000 VAC
Proof Tested:	15,000 VAC	15,000 VAC	15,000 VAC
Recommended Maximum Use Voltage:	3,000 VAC	3,000 VAC	3,000 VAC
Dimensional Stability:	0.02 in/ft (0.17 cm/m) ±	0.25 in/ft (2.10 cm/m) ±	0.25 in/ft (2.10 cm/m) ±
Resistance After Sulfuric Acid Immersion:	Pass	Pass	Pass
Resistance After Oxygen Bomb Aging:	Pass	Pass	Pass
Resistance After Light Aging:	Pass	Pass	Pass
Surface Finish:	Smooth Marbleized	Smooth	Raised Diamond Plate
Surface Gloss Level:	50	-	-
Back Finish:	Stipple	Stipple	Textured Cloth Impression
Cut:	Sheet	Runner	Mat/Runner
Color:	Beige, Black, Blue, Green, Grey, Terra Cotta	Beige, Black, Blue, Green, Grey, Terra Cotta	Beige, Black, Blue, Green, Grey, Terra Cotta
Roll Size (W x L):	36" x 75' (91.4 cm x 22.9 m)	36" x 75' (91.4 cm x 22.9 m)	36" x 75' (91.4 cm x 22.9 m)
Item ID #s:	<b>Beige</b> - NSN: #7220-01-024-9039 - Item ID: #67459039 <b>Blue</b> - NSN: #7220-01-024-9040 - Item ID: #67459040 <b>Green</b> - NSN: #7220-01-025-1695 - Item ID: #67451695 <b>Grey</b> - NSN: #7220-01-357-4133 - Item ID: #67459051 <b>Terra Cotta</b> - NSN: #7220-01-024-9041 Item ID: #67459050	<b>Beige</b> - Item ID: #67459042 <b>Blue</b> - NSN: #7220-00-267-4630 - Item ID: #67454630 <b>Green</b> - NSN: #7220-00-913-8751 - Item ID: #67458751 <b>Grey</b> - Item ID: #67459044 <b>Terra Cotta</b> - Item ID: #67459045	<b>Beige</b> - Item ID: #67459046 <b>Black</b> - Item ID: #67459047 <b>Blue</b> - Item ID: #67459053 <b>Green</b> - NSN: #7220-01-056-1944 - Item ID: #67451944 <b>Grey</b> - NSN: #7220-01-057-1897 - Item ID: #67451897 <b>Terra Cotta</b> - Item ID: #67459049

Custom sizes available upon request.



Made in the USA by RM Biltrite™ LLC, a leading US manufacturer of engineered thermoplastic products including: building materials; specialty flooring and matting; noise attenuation; gasketing; and other products with complex technical requirements.

For samples and more product information, please contact your local distributor or an RM Biltrite™ representative at 800.877.8775.



© RM Biltrite, LLC 2018

The following are trademarks of RM Biltrite, LLC: RMBiltrite™, Biltrite®, Tuff Trac®

The following are trademarks of QRRl, Inc: RubberMax™

There may be other trademarks of RM Biltrite or other companies noted in this document.

Revised April 5, 2019

Distributed by:

P: (800) 877-8775 | F: (888) 894-0204  
 sales@rmbiltrite.com | www.rmbiltrite.com  
 8525 Dunwoody Pl | Sandy Springs, GA 30350