



**Conductive Matting**  
Stipple and Diamond Finish



Protect from harmful static charge by using Tuff Trac® Conductive Matting


### Matting for Anti-Static Protection

**RM Biltrite® Tuff Trac® Conductive Matting** offers excellent anti-static protection for personnel, equipment, and products. It is engineered for use in environments with exposure to higher electrical charges and rapid rates of decay/dissipation. Matting products also provide additional foot comfort and anti-fatigue properties.

**Conductive Matting** is a necessary element to keeping electronics with sensitive components such as cash registers, computers, and machinery, safe from static damage. The matting prevents static charge from reaching vulnerable internal parts like computer chips, circuits, and motherboards.

**Tuff Trac® Conductive Matting** is manufactured from a homogeneously compounded mixture of PVC vinyl and conductive raw material. All conductive matting products are fabricated to ANSI/ESD S7. 1-2005 standards and test in the optimal electrical rating range of  $10^4$ - $10^6$ . Matting must be used with grounding clips to ensure proper safety and performance. Comes in stipple and diamond finishes (latter is available with optional yellow safety edge).

# CONDUCTIVE MATTING



TECHNICAL SPECIFICATIONS	STIPPLE FINISH	DIAMOND FINISH
<b>Thickness:</b> ASTM D412	3/32" (2.4 mm)	5/32" (4.0 mm)
<b>Tensile:</b> ASTM D412	800 psi (5.5 MPa)	800 psi (5.5 MPa)
<b>Elongation:</b> ASTM D412	150%	150%
<b>Surface Wear Resistance:</b> Taber, H-18 wheel/500 gr./1000 rev.	Good	Good
<b>Dimensional Stability:</b> ASTM D1204	Excellent	Excellent
<b>Resistance to Ground:</b> RTG/Face: ANSI/ESD S7.1-2005	10 <sup>4</sup> - 10 <sup>6</sup>	10 <sup>4</sup> - 10 <sup>6</sup>
<b>Ozone Resistance:</b> ASTM D178-01	Pass	Pass
<b>REACH &amp; RoHS:</b>	Compliant	Compliant
<b>Recommended Use:</b>	Floor	Floor
<b>Polymer:</b>	PVC	PVC
<b>Surface Finish:</b>	Stipple	Diamond
<b>Back Finish:</b>	Smooth	Textured Cloth Impression
<b>Color:</b>	Black	Black (Optional yellow safety edge)
<b>Roll Length:</b>	75' (22.9 m)	75' (22.9 m)
<b>Item ID #s:</b>  <b>Custom sizes available upon request.</b>	<b>36" (91.4 cm) wide: #67230103</b> <b>48" (121.9 cm) wide: #67230104</b>	<b>36" (91.4 cm) wide: #67230101</b> <b>+ Yellow Safety Edge: #67230014</b>  <b>48" (121.9 cm) wide: #67230102</b> <b>+ Yellow Safety Edge: #67230107</b>

Distributed by:

Made in the USA by RM Biltrite® LLC, a leading US manufacturer of engineered thermoplastic products including: building materials; specialty flooring and matting; noise attenuation; gasketing; and other products with complex technical requirements.

**For samples and more product information, please contact your local distributor or an RM Biltrite® representative at 800.877.8775.**



© RM Biltrite, LLC 2020

The following are trademarks of RM Biltrite, LLC: RMBiltrite®, Biltrite®, Tuff Trac®

The following are trademarks of QRR, Inc: RubberMax®

There may be other trademarks of RM Biltrite or other companies noted in this document.

Revised November 17, 2020

P: (800) 877-8775 | F: (888) 894-0204  
 sales@rmbiltrite.com | www.rmbiltrite.com  
 8395 Dunwoody Pl | Sandy Springs, GA 30350